

REQUIRED LABELING FOR PHOTOVOLTAIC SYSTEMS





Labeling shall comply with CEC Sections 690-5c, 690-10c, 690-17

Labels shall be printed or manufactured so as to be permanent and shall not discolor or be subject to deterioration from exterior / weather conditions. Hand written marker pen labeling will not be allowed.

WARNING

SINGLE 120 VOLT SUPPLY DO NOT CONNECT MULTI-WIRE BRANCH CIRCUITS

DISCONNECT

Photovoltaic system from utility

SINGLE SOURCE SYSTEMS ONLY TO BE PLACED ON THE PHOTOVOLTAIC SYSTEM DISCONNECT TO THE MAIN ELECTRICAL SERVICE

-WARNING-MULTIPLE POWER SOURCES

A PHOTOVOLTAIC SYSTEM

IS PRESENT.

120 VAC and / or 240VAC

may be produced.

DC power circuits

are present on this site.

Batteries may be present on this site.

Disconnect all power sources

before servicing.

Test all voltages

to confirm disconnection.

TO BE PLACED ON MAIN ELECTRICAL PANEL COVER

-WARNING-ELECTRIC SHOCK HAZARD

- Do not touch terminals Terminals on BOTH the line and load sides may be energized in the open position.

TO BE PLACED ON THE DISCONNECT FROM THE SOLAR PANELS TO THE PHOTOVOLTAIC SYSTEM